Description	Standard	Your requirements

Thermo element		
Measuring element	❍ 1 x Pt100 (par défaut) ❍ 2 x Pt100	
Precision class	❍ Class A ❍ Class AA ❍ Class B as standard	
Wire arrangement	❍ 1 x 4-wires ❍ 1 x 2-wires ❍ 1 x 3-wires as standard ❍ 2 x 2-wires ❍ 2 x 3-wires	
Temperature range	❍ -200 / 260 °C as standard ❍ Other range, please specify	

Immersion zone		
Measuring tube	❍ Other dimensions - please specify ❍ s.s. tube AISI 316 Ø6 x 100 mm ❍ s.s. tube AISI 316 Ø6 x 50 mm	
Sliding connector (option)	❍ None (standard) ❍ Sliding connector - please specify the thread ❍ Other (please specify)	

Cables		
Cable insulation c	❍ Other insulation ❍ PFA / PFA (as standard)	
Cable length	❍ 1 meter as standard ❍ Other length, please specify	
Cable termination c	❍ Connector - please specify brand and model ❍ Cable lugs	
Cable protection	❍ None (standard) ❍ Cable Sleeve Wrap ❍ Bending spring	

Cables		
	❍ Other (please specify)	

Identification		
Identification	❍ Other, please specify ❍ Self-adhesive label	
Tag plate	❍ Not required (standard) ❍ s.s. tag plate with P&ID number ❍ PVC tag plate with P&ID number	

Other requirements		
Fully watertight construction option	❍ None (standard) ❍ Watertight IP68 option	
Calibration	❍ Calibration required - please specify the temperature calibration points ❍ Not required (as standard)	
Certificates (option)	❍ None required ❍ Conformity certificate ❍ Material certificate ❍ ATEX Ex ia (intrinsic safety)with certificate	